

Hygiene detail library

Paroc Panel System


CAD-DRAWINGS



Paroc Panel Hygiene details, table of contents

CAD-DRAWINGS

DETAIL NUMBER	DESCRIPTION	PAGE NUMBER
PAROC PANEL INFORMATION		
OR-PF1	Fasteners for Paroc Panel	2
OR-E-101	Paroc Panel types	3
PAROC PANEL JOINT IN HYGIENE SOLUTIONS		
HY-C-105	Paroc Panel Ceiling joint, hygiene solution	4
HY-I-105	Paroc Panel joint in hygiene solutions, horizontal installation	5
HY-I-106	Paroc Panel joint in hygiene solutions, vertical installation	6
CEILING, HYGIENE SOLUTIONS		
HY-C-301	Paroc Panel fixing to ceiling with hat-profile	7
INTERNAL WALLS, HYGIENE SOLUTIONS		
HY-I-201	Fixing to floor, horizontally sawed panel. Horizontal installation	8
HY-I-206	Fixing to floor, horizontal or vertical installation	9
HY-I-402	Fixing in corner, vertical installation	10
HY-I-403	Fixing in corner, flashing alternatives, vertical installation	11
EXTERNAL WALLS, HYGIENE		
HY-E-202	Fixing to base, horizontal installation	12
HY-E-203	Fixing to base with penetrating fasteners, horizontal or vertical installation	13
HY-E-301	Fixing to steel frame, horizontal installation	14
HY-E-701	Installation of door, horizontal installation	15
HY-E-702	Installation of door with frame of L-profiles inside	16
HY-E-801	Installation of window or louver	17
HY-E-802	Installation of window or louver with frame of L-profile inside	18


RB


Concrete constructions
Stainless steel
Concrete screw

RB050 (50mm panel)	RB120 (120mm panel)	RB200 (200mm panel)
RB080 (80mm panel)	RB150 (150mm panel)	RB240 (240mm panel)
RB100 (100mm panel)	RB175 (175mm panel)	RB300 (300mm panel)

Stainless steel sealant washer d=22mm (also available with 19mm washer)

ATTENTION !!! Pre-drill 6,0 - 6,3 mm!


SB


Concrete constructions
Ceramic coated carbon steel
Concrete screw

SB050 (50mm panel)	SB120 (120mm panel)	SB200 (200mm panel)
SB080 (80mm panel)	SB150 (150mm panel)	SB240 (240mm panel)
SB100 (100mm panel)	SB175 (175mm panel)	SB300 (300mm panel)

Stainless steel sealant washer d=22mm (also available with 19mm washer)


ATTENTION !!! Pre-drill 6,0 - 6,3 mm!

RS


Steel constructions 1.5 - 3 mm
Stainless steel
Drilling fastener

RS050 (50mm panel)	RS120 (120mm panel)	RS200 (200mm panel)
RS080 (80mm panel)	RS150 (150mm panel)	RS240 (240mm panel)
RS100 (100mm panel)	RS175 (175mm panel)	RS300 (300mm panel)


Stainless steel sealant washer options: d=19mm, d=29mm

SS


Steel constructions 1.5 - 3 mm
Ceramic coated carbon steel
Drilling fastener

SS050 (50mm panel)	SS120 (120mm panel)	SS200 (200mm panel)
SS080 (80mm panel)	SS150 (150mm panel)	SS240 (240mm panel)
SS100 (100mm panel)	SS175 (175mm panel)	


Stainless steel sealant washer options: d=19mm, d=29mm

RM


Steel constructions 3 - 12 mm
Stainless steel
Drilling fastener

RM050 (50mm panel)	RM120 (120mm panel)	RM200 (200mm panel)
RM080 (80mm panel)	RM150 (150mm panel)	RM240 (240mm panel)
RM100 (100mm panel)	RM175 (175mm panel)	RM300 (300mm panel)


Stainless steel sealant washer options: d=19mm, d=29mm

SM


Steel constructions 3 - 12 mm
Ceramic coated carbon steel
Drilling fastener

SM050 (50mm panel)	SM120 (120mm panel)	SM200 (200mm panel)
SM080 (80mm panel)	SM150 (150mm panel)	SM240 (240mm panel)
SM100 (100mm panel)	SM175 (175mm panel)	SM300 (300mm panel)


Stainless steel sealant washer options: d=19mm, d=29mm

RW


Wood constructions
Stainless steel
Tapping fastener

RW050 (50mm panel)	RW120 (120mm panel)	RW200 (200mm panel)
RW080 (80mm panel)	RW150 (150mm panel)	RW240 (240mm panel)
RW100 (100mm panel)	RW175 (175mm panel)	RW300 (300mm panel)

Stainless steel sealant washer d=22mm (also available with d=19mm and d=29mm)


SL


Steel constructions > 1.5mm
Stainless steel
Tapping fastener


SL050 (50mm panel)	SL120 (120mm panel)	SL200 (200mm panel)
SL080 (80mm panel)	SL150 (150mm panel)	SL240 (240mm panel)
SL100 (100mm panel)	SL175 (175mm panel)	

Stainless steel sealant washer d=22mm (also available with d=19mm and d=29mm) ATTENTION !!! Predrilling needed. Drill dimension according to material thickness and steel type


Paroc Line 200




Paroc Line 150




Paroc Line 600




Paroc Smooth



Paroc Micro




Paroc Shadow



Attention!
In case of direct food contact, use
sealant type AP-TT-16!


Paroc panel



(AP-FS-11) Screw, RST c/c 300 mm


(AP-TT-13) Joint compound, transparent (applied at site)

Joint sealing, sealant compound (AP-TT-13) or factory applied sealant



Standard ceiling


External side (up)




Inside (down)

(AP-TT-12) Joint sealant, inside
applied on site.

Or factory applied sealant




(AP-TT-12) Joint sealant, inside



[X] Supplier Paroc Panel System



(AP-TT-12) Joint sealant, inside

Washable wall joint




Paroc Panel

Flat surface recommended




Take away
superfluous
material using
an empty tube

Sealant
Compound




(AP-TT-12) Joint sealant, inside



Inside

Inside



**NOTE! TT-16 to be used in
case of direct food contact!**

[X] Supplier Paroc Panel System



Paroc Panel System: **Hygiene**

Detail No.: **HY-I-106**

Type: **Internal wall**
 Subject: **Paroc Panel joint when used in food industry**
Vertical installation

Scale: **1:5**

Revision:

Date: **05/2021**

Revision Date:

Signature: **JeN**

Revision Signature:

Notice: Principle Master Detail



Project specific changes on designer's responsibility

Copyright Paroc Panel System 2019-07-01

Attention!
 In case of direct food contact, use sealant type TT-16!

Flat surface recommended


Paroc Panel




Washable wall joint

(AP-TT-12) Joint sealant, inside or TT-16 in case of direct food contact

A / B




A / B



(AP-TT-12) Joint sealant, inside or TT-16 in case of direct food contact

A / B




[X] Supplier Paroc Panel System

Attention!

See Paroc Panel System Technical Guide for protection of ceiling panels!

Attention!

In case of direct food contact, use sealant type TT-16!



[X] Supplier Paroc Panel System

Paroc Panel System:	Hygiene	Detail No.:	HY-I-201
Type:	Partition wall	Scale:	1:5
Subject:	Paroc panel fixing to floor Horizontally sawed panel Horizontal installation	Revision:	A
		Date:	02/2012
		Revision Date:	28.04.2021
		Signature:	KjN
		Revision Signature:	JeN


Notice: Principle Master Detail

Project specific changes on designer's responsibility

Copyright Paroc Panel System 2019-07-01


Information about joint sealants can be found in details OR-E-105 and OR-E-106.

Attention!
In case of direct food contact, use sealant type AP-TT-16!



Information about joint sealants can be found in details OR-E-105 and OR-E-106.

Attention!
In case of direct food contact, use sealant type AP-TT-16!



Paroc Panel System:	Hygiene	Detail No.:	HY-I-402
Type:	Internal detail	Scale:	1:5
Subject:	Paroc panel fixing in corner Vertical installation	Revision:	A
		Date:	02/2012
		Revision Date:	28.04.2021
		Signature:	KjN
		Revision Signature:	JeN

Notice: Principle Master Detail


Project specific changes on designer's responsibility

Copyright Paroc Panel System 2019-07-01

Information about joint sealants can be found in details OR-E-105 and OR-E-106.




Attention!
In case of direct food contact, use sealant type AP-TT-16!

See also detail HY-I-403




Information about joint sealants can be found in details OR-E-105 and OR-E-106.

Attention!
In case of direct food contact, use sealant type AP-TT-16!



Attention!

In case of direct food contact, use sealant type TT-16!



Paroc Panel System: Hygiene		Detail No.: HY-E-203	
Type:	Cladding Detail	Scale:	1:5
Subject:	Paroc Panel fixing to base with penetrating fasteners Horizontal or vertical installation	Revision:	A
		Date:	02/2012
		Revision Date:	28.04.2021
		Signature:	KjN
		Revision Signature:	JeN

Notice: Principle Master Detail


Project specific changes on designer's responsibility

Copyright Paroc Panel System 2019-07-01

Attention!
In case of direct food contact, use
sealant type TT-16!

Attention!
Joints always at same level for cover flashings as for horizontal panel joint!
Never install two flashings together with screws in lenght direction!

Always use a tape roller on sealant tapes to ensure maximum sealant effectivity!




Attention!

In case of direct food contact, use sealant type TT-16!

Attention!

Joints always at same level for cover flashings as for horizontal panel joint!
Never install two flashings together with screws in length direction!

Always use a tape roller on sealant tapes to ensure maximum sealant effectivity!



Information about joint sealants can be found in details OR-E-105 and OR-E-106.

Attention!

Joints always at same level for cover flashings as for horizontal panel joint!
Never install two flashings together with screws in length direction!

Always use a tape roller on sealant tapes to ensure maximum sealant effectivity!




Attention!

In case of direct food contact, use sealant type TT-16!

The ends of the short flashing must be turned up a little (as a groove)

Safety flashing L=100 mm through the vertical joint



(AP-TT-51) Flashing sealant stripe, butyl

(AP-FS-11) Flashing screw, RST c/c 300 mm

Safety flashing trough the vertical joint

(AP-FS-11) Flashing screw, RST, 1/corner

(AFPLI_) Window flashing

(AP-TT-13) Joint compound, transparent

Door frame


Paroc Panel

(AP-TT-12) Joint sealant, inside

PU-foam

(AP-TT-12) Joint sealant, inside

(TT-12) Joint sealant, inside




Paroc Panel


(AP-FS-11) Flashing screw, 1/corner

(AP-TT-13) Joint compound, transparent

Panel joint Safety flashing with vertical panels



(AP-TT-12) Joint sealant, inside








Information about joint sealants can be found in details OR-E-105 and OR-E-106.

Always use a tape roller on sealant tapes to ensure maximum sealant effectivity!



Attention!
In case of direct food contact, use sealant type TT-16!



Information about joint sealants can be found in details OR-E-105 and OR-E-106.





Attention!

Joints always at same level for cover flashings as for horizontal panel joint!
Never install two flashings together with screws in length direction!

Always use a tape roller on sealant tapes to ensure maximum sealant effectivity!


Attention!

In case of direct food contact, use sealant type TT-16!




Information about joint sealants can be found in details OR-E-105 and OR-E-106.

Attention!

Joints always at same level for cover flashings as for horizontal panel joint!
Never install two flashings together with screws in length direction!

Always use a tape roller on sealant tapes to ensure maximum sealant effectivity!


Attention!

In case of direct food contact, use sealant type TT-16!

